



GF BEARING-SINGAPORE LTD.

TYPE TS



TIMKEN 469 bearing

Bearing No. 469

469 Bearing 2D drawings and 3D CAD models

Series	455
Cone Part Number	469
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹	62900 lbf
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) ²	16300 lbf
d	2.2500 in
B - Cone Width	1.1542 in
R - Cone Backface To Clear Radius ³	0.14 in
da - Cone Frontface Backing Diameter	2.68 in
db - Cone Backface Backing Diameter	2.83 in
Ab - Cage-Cone Frontface Clearance	0.08 in
Aa - Cage-Cone Backface Clearance	0.07 in
a - Effective Center Location ⁴	-0.28 in
C90 - Dynamic Radial Rating (90 million revolutions) ⁵	9370 lbf
C1 - Dynamic Radial Rating (1 million revolutions) ⁶	36100 lbf
C0 - Static Radial Rating	37200 lbf



GF BEARING-SINGAPORE LTD.

C _{a90} - Dynamic Thrust Rating (90 million revolutions) ⁷	5380 lbf
K - Factor ⁸	1.74
G1 - Heat Generation Factor (Roller-Raceway)	58.6
G2 - Heat Generation Factor (Rib-Roller End)	17.1
C _g - Geometry Factor	0.0946